

MSHD-05N (DSTAVD115X)

1x5 D-TV Distributor

IMAGE



DEFINITION

- D-TV 신호, 컴포넌트 신호, 오디오 신호를 입력 받아 증폭·감쇄 및 왜곡 없이 분배하는 장비로, 신뢰성 Room·Show Room 등에 적합한 장비입니다.

SPECIFICATION

Input/Output Channel	1 Channel / 5 Channels
Pixel Clock	8~150MHz
Input Connector	Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA
Output Connector	Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA
Y Level Attenuation	Input(1.0Vp-p / Load 75ohm)±20mV : Level Control for VR
Pb, Pr Level Attenuation	Input(700mV / Load 75ohm)±10mV : Level Control for VR
Audio Bandwidth	20Hz~20KHz
Resolution	480i/p, 576i/p, 720p, 1080i/p for ATSC and DVB Format
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	200 X 135 X 105mm, Weight : 0.8Kg

* All specifications are subject to change without any notice.

전화. 055-297-8880 / 팩스. 055-256-7388

주소. 경남 창원시 팔용동 42-20번지 (우641-847)

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!